


# SFA-5E24SLA/CM (BK)

- Heat resistance ★★ ★
  - Oil resistance ★★ ★ ★
  - Noise resistance ★★ ★ ★
  - Flame resistance ★★ ★ ★ ★
  - non-migratory ★★ ★ ★ ★
  - Transport property ★
- ※The characteristic is an aim.

Certification	UL CM	cUL CM	UL AWM	cUL AWM
Applicable standard	UL 444	CSA C22.2 No.214	UL 758	CSA C22.2 No.210
Official symbol	CM	CM	UL STYLE 20276	CSA AWM II A/B
Voltage rating	300V	300V	30V	30V
Temperature rating	75°C	75°C	80°C	80°C
Conductor	UL 444	CSA C22.2 No.214	UL 758	CSA C22.2 No.210
Flame rating	Vertical-Tray Flame Test	Vertical-Tray Flame Test	VW-1	FT1



## CAT5e Ethernet fix cable


### > Application

- FA standard cable with UL and cUL.
- CAT5e
- Flexible cable with UL,cUL at 300V 75°C.  
(Category : DUZX,DUZX7,AVLV2,AVLV8)

### > Features

- Flame resisting : UL VW-1, cUL FT1.
- It passes Vertical-tray Flame Test of UL,cUL.
- Oil,heat flame resisting flexiblePVC material is used for sheath.
- CM listing standard is acquired and it corresponds to NFPA70.

### > Construction figure



### > Surface marking

TAIYO/TSUNET FA-5E24SLA/CM E176892-TK C(UL)US CM 24WG 75°C or AWM 20276 VW-1 or AWM II A/B 80°C 30V FT1 LF R15 length mark

※R15 indicates "Compliant with RoHS Directive 2011/65/EU and Directive (EU) 2015/863 (10 substances)".

### > Identification

Pair number	1	2	3	4
No.1 kind line	Blue/White	Orange/White	Green/White	Brown/White
No.2 kind line	Blue	Orange	Green	Brown

※Blue/White : Blue line is marked on white insulation.

### > Construction table

No. of pairs	Conductor		Polyethylene insulation		Oil,heat-resistant flexible-PVC sheath		Approx. weight (lbs/1000ft) (kg/km)	Electrical Characteristics		
	Size (AWG)	Construction (Line/mm)	Outside diameter (inch)	Outside diameter (mm)	Overall diameter approx.(inch)	Overall diameter approx.(mm)		Conductor resistance (Ω/km20°C)	Insulation resistance (MΩkm20°C)	Electrical strength (V/1min.)
4P	24	SOLID	0.041	1.03	0.260	6.6	30(45)	less than 93.8	more than 5,000	AC700

### > Electric characteristics (High Frequency)

Electric Characteristics	Frequency (MHz)				
	1	4	16	31.25	100
Insertion Loss (dB/100m)	less than 2.0	less than 4.1	less than 8.2	less than 11.7	less than 22.0
NEXT loss (dB)	more than 65.3	more than 56.3	more than 47.2	more than 42.9	more than 35.3
PSNEXT Loss (dB)	more than 62.3	more than 53.3	more than 44.2	more than 39.9	more than 32.3
Characteristic Impedance (Ω)	85-115				

### > Standard sales length

200m