

EM-TXT HF

Flame resistant flexible cross-linked polyethylene insulated wire for electrical equipment

Heat resistance	★★★★★
Oil resistance	★
Noise resistance	★
Flame resistance	★★★
Flexibility	★★★★★
non-migratory	★★★★★
Transport property	★
※The characteristic is an aim.	

>>> Meeting standard



Certification	Electrical Appliance and Material Safety
Applicable standard	Law/Departmental order to determine a technical standard of the electrical equipment
Official symbol	EM-KIE/F
Voltage rating	600V
Temperature rating	75°C
Conductor	JIS C 3102
Flame rating	JIS C 3005-4.26.2-b)


Application

- 600V electrical equipment wiring.
- Flame resistant cross-linked polyethylene. (Halogen-free.)
- Rated voltage:600V. Heat resistance:125°C.※¹
(1500V type can be products. Please contact us for details.)
- ※¹ 125°C(Temperature in CMJ registered materials.)

Feature

- Flexible annealed copper stranded conductor.
- Non-halogen flame resistant flexible cross-linked polyethylene for insulation.
- Low smoke evolution.
- Minimum bending radius is 2D
(Only when used for fixing)
- Heat resistance 125 °C.※¹ ※² ※³
- Cold -40 °C.
- Conform to Electrical Appliance and Material Safety Law.
- UL VW-1(Equivalent material). (8mm²~)

Construction figure



Surface marking



Identification

- Black

Construction table

No. of cores	Conductor			Flame resistant flexible cross-linked polyethylene insulation		Approx. weight (lbs/1000ft) (kg/km)	Electrical Characteristics			Allowable ampacity (A)※ ²	Allowable ampacity (A)※ ³
	Size (SQ) (mm ²)	Construction (Line/mm)	Outside diameter (mm)	Outside diameter (inch)	Outside diameter (mm)		Conductor resistance (Ω/km20°C)	Insulation resistance (MΩkm20°C)	Electrical strength (V/1min.)		
1C	5.5	70/0.32 (70/12.6mil)	3.1 (12.2mil)	0.201	5.1	55(37)	less than 3.27	more than 50	1500	86	69
1C	8	98/0.32 (98/12.6mil)	3.7 (14.6mil)	0.225	5.7	95(64)	less than 2.32	more than 50	1500	108	86
1C	14	172/0.32 (172/12.6mil)	4.9 (19.3mil)	0.272	6.9	155(104)	less than 1.32	more than 40	2000	156	124
1C	22	7/39/0.32 (7/39/12.6mil)	6.7 (26.4mil)	0.359	9.1	250(167)	less than 0.844	more than 40	2000	204	162
1C	38	7/67/0.32 (7/67/12.6mil)	8.8 (34.6mil)	0.441	11.2	410(274)	less than 0.496	more than 40	2500	288	228
1C	60	19/39/0.32 (19/39/12.6mil)	11.2 (44.1mil)	0.559	14.2	650(434)	less than 0.311	more than 30	2500	386	306
1C	80	19/52/0.32 (19/52/12.6mil)	13.1 (51.6mil)	0.634	16.1	850(567)	less than 0.230	more than 30	2500	480	380
1C	100	19/67/0.32 (19/67/12.6mil)	14.7 (57.9mil)	0.737	18.7	1120(747)	less than 0.183	more than 30	2500	530	420

Allowable ampacity

• The allowable ampacity of this catalog is a value at one in the air construction and the ambient temperature 30°C.

※² Allowable current for inside equipment use.(Permissible conductor temperature is 125°C.)

※³ All current for power-supply use.(Conductor allowable temperature is 90°C.)

• Please multiply the following correction coefficient by the ambient temperature and the cable-laying conditions, etc.

● Adjustment factors(Temperature during use in equipment.)

Ambient temperature(°C)	30	40	50	60	70	80	90	100	110	120
Adjustment factors	1.00	0.95	0.89	0.83	0.76	0.69	0.61	0.51	0.40	0.23

● Adjustment factors(Cases used for power supply, etc.)(Use temperature upper limit 90°C.)

Ambient temperature(°C)	30	40	50	60	70	80
Adjustment factors	1.00	0.91	0.82	0.71	0.58	0.41

● Adjustment factors(for multiple-line laying)

No. of conductors	2~3	4	5~6	7~15	16~40	41~60	61~
Adjustment factors	0.70	0.63	0.56	0.49	0.43	0.39	0.34
No. of conductors in the same tube	~3	4	5 or 6	7~15	16~40	41~60	61~
Adjustment factors	0.70	0.63	0.56	0.49	0.43	0.39	0.34

Standard sales length

100m

(38,60 and 100mm² can support in short length less than 100m. Please contact us.)